

HPE Networking Comware Switch Series 5140 HI

HPE Networking Comware Switch 48G PoE+ 4SFP+ 1-slot 5140HI (R9L64A)



What's new

- Gigabit Ethernet access switch with intermediate L3 routing features such as OSPF V2 / OSPF V3 / VRRP / VRRPE / Routed Ports, RIP, 10GbE uplinks, and PoE+ models for voice, video, and wireless.
- Higher port switching capacity, forwarding performance and port line rate granularity, 2X dynamic ARP, 2X IPv6 unicast routing, and introduction of IGMP proxy for improved performance.
- DRNI combines multiple physical switches into one virtual distributed-relay (DR) system for doubling aggregate bandwidth, faster forwarding, resiliency, and high availability.
- Intelligent Network Quality Analyzer (iNQA) measures network packet loss performance and provides visibility

Overview

The HPE Networking Comware Switch Series 5140 HI delivers high availability and scalability at the access layer of medium and large enterprise campus networks.

These switches offer high speed connectivity and flexibility with 10GbE uplinks and combo ports. Support for add-on modules increases capacity with additional features. It is a highly cost-effective switch with abundant features such as DRNI and IRF for improved resiliency, QoS features for better reliability, iNQA for real time network health performance and capacity visibility, hardware-based MACsec for end-to-end encrypted security, and dual redundant power supplies with Energy Efficient Ethernet for improved power saving.

This switch series also includes Smart MC at no additional cost and, when combined with Intelligent Management Center (IMC), provides both embedded network management and enhanced network visibility.

into real-time application performance and health.

- Industry standard AES 256 MACsec support, higher MAC port binding and link group capacity for improved end-to-end network security. 2-port AES256 MACsec module R9L65A has been introduced.
- Smart Management Center (SmartMC) provides centralized network management and maintains dispersed network edge devices at no additional cost.

Features

Highly Resilient and Scalable Access Layer Switches

The HPE Networking Comware Switch Series 5140 HI uses Intelligent Resilient Framework (IRF) to support virtualization of up to nine physical switches into one logical device for simpler, flatter, and more agile networks.

Supports 10GbE uplinks, static and RIP routing, PoE+, ACLs, and IPv6 for improved and cost-effective network performance.

DRNI enables link aggregation from multiple switches to implement device-level link backup for node redundancy. DRNI also simplifies network topology by virtualizing two physical devices into a logical device.

iNQA helps in measuring network packet loss performance, forward, reverse, and two-way packet loss, including lost number of messages and bytes, message loss, and byte loss rate.

Dual, redundant, hot-swappable power supplies maintain a dynamic and highly available network switch, delivering up to 1440 Watts of PoE+ for powered cameras, phones, and wireless Access Points.

Robust Quality of Service (QoS)

The 5140 HI Series supports advanced classifier-based QoS which groups traffic using multiple match criteria based on Layer 2 and 3 information; it applies QoS policies such as setting priority level and rate limit to selected traffic on a port, VLAN, or the entire switch.

Provides extensive traffic prioritization with strict priority (SP) queuing, weighted round robin (WRR), and SP+WRR.

Broadcast control and limitation of broadcast traffic rate can reduce unwanted network traffic and preserve more bandwidth for critical data.

Comprehensive Security Control

The 5140 HI Series supports flexible authentication methods including 802.1X, MAC Authentication and Encryption for greater device security and policy-driven application authentication. Per-user Access Control Lists (ACLs) provide identity-driven security and access control.

Dynamic ARP protection with functions such as ARP Detection and ARP packet validation blocks broadcast from unauthorized hosts and prevents eavesdropping or theft of network data.

Supports industry standard AES256 MACsec which provides increased MAC port binding and link group capacity for greater end-to-end security.

Centralized security policy management and network protection with HPE Intelligent Management Center (IMC) which leverages End User Admission Domination (EAD) integrated security policies, network access control and access right control policies to provide a comprehensive integrated security system.

Security with encryption of all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3, and other features including DHCP protection, IP source guard, dynamic ARP protection, and RADIUS/HWTACAS.

Simplified Management

The 5140 HI Series can be seamlessly managed with HPE Intelligent Management Center (IMC) Software to provide end-to-end network transparency with consistent network experience through comprehensive configuration, compliance, and policy management.

Supports SmartMC, an embedded network management tool, with a web-based GUI to simplify operations and facilitate centralized management at no additional cost. It offers features such as configuration backup, software version management, and seamless switch replacement.

RMON and sFlow® provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events to help network operators with capacity planning and real-time network monitoring.

Technical specifications		HPE Networking Comware Switch 48G PoE+ 4SFP+ 1-slot 5140HI
Product Number	R9L64A	
Differentiator	48 fixed 10/100/1000Base-T PoE+ Ports 4 fixed SFP+ Ports (min=0 \ max=4 SFP/SFP+ Transceivers) 1 port expansion module slot Must select min 1/ max 2 power supply Includes 2 Fan Trays 1U - Height	
Power consumption	1742 W (dual AC) 1440W (PoE power)	
Input voltage	100VAC–240VAC, 48 to -60VDC Maximum, depending on model and configuration	
External I/O ports	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+) 4 SFP+ 10GbE ports 1 port expansion module slot	
Latency	< 5 microseconds (64-byte packets)	
Switching capacity	336 Gbps	
Stacking capabilities	IRF 9 switches	
Throughput	180 Mpps	
Memory and processor	2 GB SDRAM Packet buffer size: 4 MB, 512 MB flash	
Power supply name	2 power supply slots 1 minimum power supply required	
PoE capability	720W (PoE power), 1440W (PoE power) depending on the model	
Management features	HPE IMC Smart MC, command-line interface web browser SNMP manager	
Weight	5.8 kg	
Product dimensions	4.37 x 44 x 46 cm	
Warranty	Limited lifetime warranty. See the warranty duration guide.	

HPE Services

No matter where you are in your transformation journey, you can count on HPE Services to deliver the expertise you need when, where and how you need it. From strategy and planning to deployment, ongoing operations and beyond, our experts can help you realize your digital ambitions.

Advisory & Professional services

Experts can help you map out your path to hybrid cloud and optimize your operations.

Managed services

HPE runs your IT operations, giving you unified control, so can focus on innovation.

Support services

Optimize your entire IT environment and drive innovation. Manage day-to-day IT operational tasks while freeing up valuable time and resources.

- **HPE Complete Care Service:** a modular service designed to help optimize your entire IT environment and achieve agreed upon IT outcomes and business goals. All delivered by an assigned team of HPE experts.
- **HPE Tech Care Service:** the operational service experience for HPE products. The service provides access to product specific experts, an AI driven digital experience, and general technical guidance to help reduce risk and search for ways to do things better.
- **HPE Multivendor Services:** Single point of accountability for managing on-site hardware and software support for multivendor products. HPE experts help manage your IT across technologies and platforms for HPE and non-HPE technologies, acting as the single point of contact for your IT operational needs.

Lifecycle Services

Address your specific IT deployment project needs with tailored project management and deployment services.

HPE Education Services

Training and certification designed for IT and business professionals across all industries. Create learning paths to expand proficiency in a specific subject. Schedule training in a way that works best for your business with flexible continuous learning options

Defective Media Retention is optional and allows you to retain Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

HPE GreenLake

[HPE GreenLake edge-to-cloud platform](#) is HPE's market-leading as-a-Service offering that brings the cloud experience to apps and data everywhere – data centers, multi-clouds, and edges – with one unified operating model, on premises, fully managed in a pay per use model.

If you are looking for more services, like **IT financing solutions**, please [explore them here](#).

[For additional technical information, available models and options, please reference the QuickSpecs](#)

Visit [HPE.com](https://www.hpe.com)

[Chat now](#)

© Copyright 2025 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

sFlow® is a registered trademark of INMON Corporation in the United States and/or other countries.

Image may differ from the actual product.

[PSN1014655839CZEN](#), November 02, 2025.

HEWLETT PACKARD ENTERPRISE

[hpe.com](https://www.hpe.com)

