

SMART SERIES

PSF-400B // SLEEVED // 400WATT



Product: PSU

Form factor: PSII

Color: silver

The PSF-400B from its layout may remind on "fore gone" ATX standards but, compatible with all current standards and certified by TÜV amongst many others and with a fixed voltage of 110-230V being the European standard, the PSF-400B is a reliable and efficient companion for modern IT structures which thereby also fulfills all ENERGY STAR 5.0 requirements as stipulated by the EU.

Dedicated majorly to the 19" IPC / UNC solutions ranging between 2U ~ 4U where the PSU position is delicate and/or tricky and the cooling fan MUST blow out the rear owing to highly limited height issues of the related chassis.

Certificates:



Technical data

Specification: ATX 12V 2.3

Efficiency: ~ 85%

Dimensions (DxWxH): 140 mm x 150 mm x 87 mm

PCF: Active PFC

Fan: 80mm fan

Connectors

24PIN	8PIN EPS (4+4)	SATA	Molex	Floppy	6PIN PCIe		
1	1	4	3	1	1		

DC Output / AC Input

AC INPUT: 110V - 230V / 6A FREQUENCY: 47 - 63HZ MAX. LOAD: 400W	DC OUTPUT								
	+5V	+3,3V	+12V1	+12V2	+12V3	+12V4	P.F.	-12V	+5VSB
	15A	16A	30A	N/A	N/A	N/A	>0,9	0,3A 3,6W	2,5A 12,5W
	120W		360W		N/A				

Security: UVP; OVP; SCP; OPP; AFC;

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.