Fujitsu recommends Windows 11 Pro.



Data Sheet FUJITSU Desktop ESPRIMO G5011

Mini, Mighty | Takes up your challenges, not your space

The FUJITSU ESPRIMO G5011 is a stylish mini PC which offers desktop functionality in an ultracompact, space-saving design. Latest Intel chipset along with 10th or the latest 11th Gen Intel® Core™ processors provides the performance for daily office needs. It supports flexible mounting options - attach to displays, wall mount, under table mount. Its compact size and wide range of interfaces make it an ideal device where space saving is critical for the business.

A stylish mini PC with ultra-compact design

Small footprint; energy and space-saving device for clean, clutter-free desk

- Fully equipped PC with a volume of only ~0.86 liters
- Impressive performance/volume ratio and is easy to set up in minutes

Ultimate usability

Flexible mounting options and wide range of usage scenarios

- Can be used for horizontal or vertical operations and easy upgrade of major components
- VESA mount for attaching the PC to displays, stands or walls

Small yet grand

High performance in a small mini PC design

- Latest Intel chipset technology along with 10th or the latest 11th generation Intel® Core™ processor family
- Legacy support for standard mini PC interfaces- DisplayPort, HDMI

Perfect fit for modern offices and workplaces of tomorrow

The PC which can transform your workplace for the next generation

- Supports new workplace scenarios with a single Type-C connection
- Type-C Docking port for future workplace and AiO-like usage

Feature-rich and energy-efficient

Do a lot more with this mini-PC and also get lesser energy bill

- Improved energy efficiency
- Next generation INTEL integrated graphics
- Type-C connector with convenient front access to support modern peripherals like Type-C USB sticks or headsets













Components

| | ESPRIMO G5011 | ESPRIMO G5011 ESTAR | |
|--------------------------------|--|--|--|
| Processor | 1.40 GHz, 16 MB, Intel® UHD Graphics 750) ** Intel® Core™ i7-10700T processor (8 Cores / 16 Threads, 2.00 GHz, 16 MB, Intel® UHD Graphics 630) ** Intel® Core™ i5-11500T processor (6 Cores / 12 Threads, 1.50 GHz, 12 MB, Intel® UHD Graphics 750) * Intel® Core™ i5-10600T processor (6 Cores / 12 Threads, 2.40 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10500T processor (6 Cores / 12 Threads, 2.30 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10400T processor (6 Cores / 12 Threads, 2.00 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i3-10105 processor (4 Cores / 8 Threads, 3.70 GHz, 6 MB, Intel® UHD Graphics 630) * Intel® Pentium® Gold G6400 (2 Cores / 4 Threads, 4.00 GHz, 4 MB, Intel® UHD Graphics 610) | GHz, 6 MB, Intel® UHD Graphics 630) * | |
| | *with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload and other variables) | | |
| Operating systems | | | |
| Operating system pre-installed | Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home | Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home | |
| Operating system compatible | Windows 11 Windows 11 Pro. Fujitsu recommends Windows 11 Pro. FREE Upgrade to Windows 11 when available. The Windows 11 upgrade will be delivered to qualifying devices late 2021 into 2022. Timing varies by device. Certain features require specific hardware (see https://www.microsoft.com/windows/windows-11-specifications) Commercial customers should check with their IT department for their rollout plan. | Windows 11 Windows 11 Pro. Fujitsu recommends Windows 11 Pro. FREE Upgrade to Windows 11 when available. The Windows 11 upgrade will be delivered to qualifying devices late 2021 into 2022. Timing varies by device. Certain features require specific hardware (see https:// . www.microsoft.com/windows/windows-11-specifications) Commercial customers should check with their IT department for their rollout plan. | |
| Operating system notes | Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – | Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – s depending on the available extension of hardware service through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com. | |
| | ESPRIMO G5011 | ESPRIMO G5011 ESTAR | |
| Memory modules | 32 GB (module(s) 32 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 16 GB (module(s) 16 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 8 GB (module(s) 8 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 4 GB (module(s) 4 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM | 32 GB (module(s) 32 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 16 GB (module(s) 16 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 8 GB (module(s) 8 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 4 GB (module(s) 4 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM | |
| | ESPRIMO G5011 | ESPRIMO G5011 ESTAR | |
| Graphics | | | |
| | ESPRIMO G5011 | ESPRIMO G5011 ESTAR | |
| | HDD SATA III, 5,400 rpm, 2000 GB, 2.5-inch | HDD SATA III, 5,400 rpm, 2000 GB, 2.5-inch | |

Page 2 / 8 www.fujitsu.com/emeia/ESPRIMO

| SSD PCIe, 1024 GB M.2 NVMe module (Gen4), SED SSD PCIe, 128 GB M.2 NVMe module (Value) SSD PCIe, 256 GB M.2 NVMe module (Gen4), SED SSD PCIe, 256 GB M.2 NVMe module (Value) SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED SSD PCIe, 512 GB M.2 NVMe module (Value) | SSD PCIe, 1024 GB M.2 NVMe module (Gen4), SED SSD PCIe, 128 GB M.2 NVMe module (Value) SSD PCIe, 256 GB M.2 NVMe module (Gen4), SED SSD PCIe, 256 GB M.2 NVMe module (Value) SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED SSD PCIe, 512 GB M.2 NVMe module (Value) |
|---|--|
| One Gigabyte equals one billion bytes, when referring to he SSD (Solid State Disk) SED (Self-Encrypting Drive) 2.5-inch bay for devices with 7mm height | ard disk drive capacity. |
| ESPRIMO G5011 | ESPRIMO G5011 ESTAR |
| | |
| ESPRIMO G5011 | ESPRIMO G5011 ESTAR |
| Intel® WI-FI 6 AX210 and Bluetooth 5.2 vPro, SRD 5.8GHz (dedicated regions only) | Intel® WI-FI 6 AX210 and Bluetooth 5.2 vPro, SRD 5.8GHz (dedicated regions only) |
| ESPRIMO G5011 | ESPRIMO G5011 ESTAR |
| The listed product components and optional functions are not available in all region/countries | The listed product components and optional functions are not available in all region/countries; Energy Star certification only with Windows operating system base unit for TCO Certified generation 8 |
| | SSD PCIe, 128 GB M.2 NVMe module (Value) SSD PCIe, 256 GB M.2 NVMe module (Gen4), SED SSD PCIe, 256 GB M.2 NVMe module (Value) SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED SSD PCIe, 512 GB M.2 NVMe module (Value) One Gigabyte equals one billion bytes, when referring to his SSD (Solid State Disk) SED (Self-Encrypting Drive) 2.5-inch bay for devices with 7mm height ESPRIMO G5011 Intel® WI-FI 6 AX210 and Bluetooth 5.2 vPro, SRD 5.8GHz (dedicated regions only) ESPRIMO G5011 The listed product components and optional functions are |

Base unit

| Base unit | ESPRIMO G5011 | ESPRIMO G5011 ESTAR |
|-------------------------------|---|---------------------|
| Mainboard | | |
| Mainboard type | D3904 | |
| Formfactor | proprietary | |
| Chipset | Intel® H510 | |
| Processor socket | LGA 1200 | |
| Processor quantity maximum | 1 | |
| Supported capacity RAM (max.) | 64 GB | |
| Memory slots | 2 DIMM (DDR4) | |
| Memory frequency | 3,200 MT/s | |
| Memory notes | Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 3200 MHz may be clocked down to 2933/2400MHz depending on processor and memory configuration | |
| LAN | 10/100/1,000 MBit/s Realtek RTL8111H | |
| Integrated WLAN | optional; WLAN 802.11ax/Wi-Fi 6 and Bluetooth 5.2 | |
| BIOS version | AMI Aptio V UEFI Specification 2.6 | |
| BIOS features | BIOS Flash EPROM update by softwa Recovery BIOS Unified Extensible Firmware Interfac | |
| Audio type | On board | |
| Audio codec | Realtek ALC623 | |
| Audio features | Internal speaker supports audio playback, High Definition audio | |
| I/O controller on board | | |
| Serial ATA total | 1 | |
| thereof SATA III | 1 | |

| I/O controller on board | | | |
|--------------------------------|--|---|--|
| Controller functions | Serial ATA III (6 Gbit) NCQ | | |
| | AHCI | | |
| Interfaces | | | |
| Front audio: headset | 1 | | |
| USB 2.0 total | 3 | | |
| USB 3.2 Gen1 (5 Gbps) total | 4 | | |
| USB front | 1x USB 3.2 Gen 1 1x USB 3.2 Gen 1 Type-C (provides up to 15W) | | |
| USB rear | 3x USB 2.0 1x USB 3.2 Gen 1 1x USB 3.2 Gen 1 Type-C (supports DisplayPort 1.4 and incl. 60W power delivery sink support e.g. from a display) | | |
| VGA | optional: via external active adapter cable | | |
| DisplayPort | 1 | | |
| HDMI | 1 | | |
| Ethernet (RJ-45) | 1 | | |
| Interface Module notes | Anytime USB charge functionality, HDMI Ver. 1.4 (with 11th generation CPUs: Ver. 2.0) | | |
| Kensington Lock support | 1 | 1 | |
| Input device / components | | | |
| Input devices (optional) | Keyboard Mouse | | |
| Drive bays | | | |
| Drive bays total | 1 | | |
| 2.5-inch internal bays | 1 | | |
| M.2-2280 | 1 x on mainboard for SSD NVMe (PCle 3.0 x4; up to 32Gbit/s) | | |
| Mini PCI slots | | | |
| M.2-2230 | on mainboard for WLAN module | | |
| Graphics on board | | | |
| Graphics brand name | Intel® UHD Graphics 730, Intel® UHD Graphics 750, Intel® UHD Graphics 610, Intel® UHD Graphics 630 | | |
| Shared video memory | Up to half size of total system memory | | |
| TFT resolution (DisplayPort) | Up to 4,096 x 2,304 pixel | | |
| TFT resolution (HDMI) | up to 4,096 x 2,160 | | |
| Graphics features | Dual display support DirectX® 12 HDCP support OpenCL™ 2.1 OpenGL® 4.5 DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W) | | |
| Graphics notes | up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz | | |
| Base unit | ESPRIMO G5011 ESTAR | | |
| Electrical values | | | |
| Power efficiency note | power supply efficiency at 115/230V: 89% average efficiency | | |
| Rated voltage range | 100 V - 240 V | | |
| Rated frequency range | 50 Hz - 60 Hz | | |
| Operating voltage range | 90 V - 264 V | | |
| Operating line frequency range | 47 Hz - 63 Hz | | |

| Electrical values | | |
|--|---|---|
| Max. output of single power supply | 65 W | |
| Base unit | ESPRIMO G5011 | ESPRIMO G5011 ESTAR |
| Power consumption | | |
| Power consumption note | See white paper Energy Consumption | See white paper Energy Consumption |
| Link to Energy White Paper | https://docs.ts.fujitsu.com/dl.aspx?id=9a164a82-6707- 4511-849b-0f5bc28ba1ab | |
| Noise emission | | |
| Related Processors for noise | Intel® Core™ i5-10500T processor and 8GB, no ODD, Windows 10 (tower position) | Intel® Core™ i5-10500T processor and 8GB, no ODD, Windows 10 (tower position) |
| Standard noise emission | According to ISO 7779:2010, ECMA-74 | According to ISO 7779:2010, ECMA-74 |
| Standard noise notes / description | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) |
| Standard noise operation mode: CPU 50% load | 3.1 B / 18 dB(A) Bystander; 20 dB(A) Operator position (SSD M.2) | 3.1 B / 18 dB(A) Bystander; 20 dB(A) Operator position (SSD M.2) |
| Standard noise operation mode: HDD load | 3.2 B / 20 dB(A) Bystander; 21 dB(A) Operator position (SSD M.2) | 3.2 B / 20 dB(A) Bystander; 21 dB(A) Operator position (SSD M.2) |
| Standard noise operation mode: Idle mode | 3.0B / $17dB(A)$ By stander; 18 dB(A) Operator position (SSD M.2) | 3.0 B / 17 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2) |
| Standard noise operation mode: Office applications 2.0 | 3.0~B/18~dB(A) By stander; 19 dB(A) Operator position (SSD M.2) | 3.0 B / 18 dB(A) Bystander; 19 dB(A) Operator position (SSD M.2) |
| Dimensions / Weight / Environmental | | |
| Dimensions (W x D x H) | 146.9 x 164.5 x 36 mm | |
| | 5.78 x 6.48 x 1.42 inch | |
| Operating position | Vertical / horizontal (feet included) | |
| VESA mount | optional mounting kit | |
| Weight | 0.8 kg | |
| Weight (lbs) | 1.76 lbs | |
| Weight notes | Actual weight may vary depending on configuration | |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) | |
| Operating relative humidity | 5 - 85 % (relative humidity) | |
| Compliance | | |
| Product | ESPRIMO G5011 | ESPRIMO G5011 ESTAR |
| Model | TCS5 | |
| Germany | GS TÜV NRTL | |
| Europe | CE | |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0 EPEAT® Silver (dedicated regions) TCO Certified 8.0 |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates | |
| Additional Software | | |
| Additional software (preinstalled) | Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial preinstalled) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) | |

Page 5 / 8 www.fujitsu.com/emeia/ESPRIMO

| Additional Software | | |
|--------------------------------|---|--|
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the re in which it was acquired.) | |
| Base unit | ESPRIMO G5011 | ESPRIMO G5011 ESTAR |
| Security | | |
| Physical Security | Kensington Lock support | Kensington Lock support |
| System and BIOS Security | Embedded security (TPM 2.0) EraseDisk | Embedded security (TPM 2.0) EraseDisk |
| | Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby ready (for configurations with Gen4 NVMe SSD and w/o PCIe cards) Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces | Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby ready (for configurations with Gen4 NVMe SSD and w/o PCIe cards) Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces |
| User Security | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) AuthConductor Client Basic (secure authentication solution) | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional AuthConductor Client Basic (secure authentication solution) |
| Manageability | | |
| Manageability technology | DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) | |
| Manageability software | DeskView Client DeskView Instant BIOS Management | |
| DeskView components | BIOS Management incl. Security Inventory Management Driver Management Alarm Management | |
| Supported standards | DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model) | |
| Manageability link | http://www.fujitsu.com/fts/manageability | |
| Miscellaneous | | |
| | Keyboard on (Special Fujitsu keyboard required) Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards Keyboard on with any key (USB) Thermal management Extended lifetime | Keyboard on (Special Fujitsu keyboard required) Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards Keyboard on with any key (USB) Thermal management Extended lifetime |

| Miscellaneous | | |
|--|---|---|
| Accessories information | Further helpful options | Further helpful options |
| | Desktop Accessories: | Desktop Accessories: |
| | http://www.fujitsu.com/global/products/computing/ | http://www.fujitsu.com/global/products/computing/ |
| | peripheral/accessories/desktop/ | peripheral/accessories/desktop/ |
| | http://www.fujitsu.com/global/products/computing/ | http://www.fujitsu.com/global/products/computing/ |
| | peripheral/accessories/connectivity/ | peripheral/accessories/connectivity/ |
| | Stands and Mounting kits: | Stands and Mounting kits: |
| | http://www.fujitsu.com/global/products/computing/ | http://www.fujitsu.com/global/products/computing/ |
| | peripheral/accessories/desktop/ums/index.html | peripheral/accessories/desktop/ums/index.html |
| | Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/ Publications/public/pos-connectivity.pdf | Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/ Publications/public/pos-connectivity.pdf |
| Packaging information | | |
| Packaging dimension (mm) | 395 x 197 x 288 mm | 395 x 197 x 288 mm |
| Packaging dimension (inch) | 15.55 x 7.76 x 11.34 inch | 15.55 x 7.76 x 11.34 inch |
| Max. quantity / pallet | 72 | 72 |
| Material - Weight (g) Carton | 650 g | 650 g |
| Material - Weight (lbs) Carton | 1.43 lbs | 1.43 lbs |
| Material - Weight (g) PE | 80 g | 80 g |
| Material - Weight (lbs) PE | 0.18 lbs | 0.18 lbs |
| Packaging notes | If keyboard is included in packaging: 1.)packaging dimension is increasing to: 497 x 206 x 293mm / (19.6 x 8.11 x 11.5 inch); 2.) material weight of carton will increase to 850g; 3.) max. quantity/pallet = 42; printed user documentation is bleached in chlorin free process; | If keyboard is included in packaging: 1.)packaging dimension is increasing to: 497 x 206 x 293mm / (19.6 x 8.11 x 11.5 inch); 2.) material weight of carton will increase to 850g; 3.) max. quantity/pallet = 42; printed user documentation is bleached in chlorin free process; |
| | Bulk packagaging for projects (optional) | Bulk packagaging for projects (optional) |
| Warranty | | |
| Warranty period | 1 year | |
| Warranty type | Bring-In / Onsite Service (depending on country) | |
| Warranty Terms & Conditions | http://www.fujitsu.com/warranty | |
| Product Support Services - the perfect e | | |
| Recommended Service | 9x5, Onsite Response Time: Next Business Day | |
| Spare Parts availability | 5 years | |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support- | services/ |

Recommended Accessories

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO G5011, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO G5011, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use. html

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2021-11-06 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH