

# Data Sheet

## Fujitsu PRIMERGY RX2530 M7 Rack Server


### Maximum productivity in a 1U housing

Fujitsu offers a fantastic blend of systems, solutions and expertise to guarantee maximum productivity, efficiency and flexibility, delivering confidence and reliability. Fujitsu PRIMERGY servers deliver workload-optimized x86 industry standard systems for any workload and business demand. Since there is no single server solution to meet all these needs, Fujitsu offers a broad server portfolio consisting of expandable tower servers, versatile rack-mount servers, density-optimized multi-node servers as well as GPU servers purpose-built for the demands of AI and VDI. While all these systems are designed to handle multiple workloads, each server is optimized for specific use cases. Whatever the size of your business – large enterprise with multiple sites, or a small or medium-sized company with limited space and budget – with the right choice of server, your IT can become the business enabler you have always wanted it to be.

#### PRIMERGY RX2530 M7

The Fujitsu PRIMERGY RX2530 M7 server in a dense 1U chassis is based on a dual-socket x86 platform providing an ideal combination of performance and scalability for most data centers. The PRIMERGY RX2530 M7 is ideal for AI workloads, HPC infrastructures, virtualization, databases as well as scale-out scenarios. It supports the latest 4th generation Intel® Xeon® Scalable Processors with up to 60 cores in a standard socket and four UPI 2.0 links resulting in a performance improvement of more than 40% compared to the previous generation processors. New High Bandwidth Memory (HBM) with up to 1 TB/s support the performance boost. The integration of Compute Express Link (CXL) supports 4x 16 devices and provides a large amount of memory capacity 8 TB (DDR5) with 32 DIMM slots delivering once more excellent results for even the most demanding applications and workloads. The new DDR5 DIMM modules provide

fast memory for intensive workloads such as data analytics and in-memory databases. Get a broad choice for storage flexibility with up to 4x 3.5" SAS/SATA, up to 10x 2.5" SAS/SATA/NVMe storage devices. In addition, two further 2.5" storage devices are available as an option on the rear of the chassis. The PRIMERGY RX2530 M7 supports the new PCIe 5.0 interface and SAS 24G for upcoming devices. A total of three such interfaces are available. It also provides two onboard LAN adapters via OCP v3. With Platform Firmware Resilience (PFR) functionality, as one example of integrated security for all servers and proven reliability help to provide a maximum uptime in enterprise data centers. Optionally available is a front locking bezel to avoid unauthorized physical access directly in the data center. All new and optimized security features should help to secure sensitive workloads and enable new opportunities to unleash the power of data. With the Fujitsu Infrastructure Manager (ISM) as well as the integrated next generation Remote Management Controller (iRMC S6), even more complex workloads and administration tasks are simplified for transparent management of your server and the IT infrastructure so you can focus on your business objectives. With the now available short chassis version, please be aware that configuration options are different for the short depth model.



# Features & Benefits

Main Features	Benefits
<p><b>OPTIMIZED PERFORMANCE AND DENSITY</b></p> <ul style="list-style-type: none"> <li>Wide choice of different available types of 4th Generation Intel® Xeon® Scalable processors. Each processor offers up to 60 cores (depending on SKU), 16 memory channels, up to 4 Intel® Ultra Path Interconnect (UPI 2.0 at 16 GT/s) and PCI-Express 5.0 with up to 80 lanes (per socket) enabling a significantly higher performance and efficiency.</li> </ul>	<ul style="list-style-type: none"> <li>Ideal dual-socket platform for dense scale-out data center computing powered by latest 4th Generation Intel® Xeon® Scalable Processors with up to 60 cores per CPU.</li> <li>Combine performance and versatility to adapt to a variety of applications and meet future demands with 32 DIMM modules and up to 8 TB of memory. DDR5 DIMM memory provides fast, high capacity for memory intensive workloads.</li> <li>Benefit from the flexibility of 2.5", 3.5" storage devices for highest capacities with up to 10 drives per height unit (U) and additional expandability with up to 3 PCIe 5.0 / 1x PCIe 4.0 (for Internal RAID controller) slots flexible adapters via OCP v3.</li> <li>Benefit from advanced security technologies such as Platform Firmware Resilience (PFR) to protect the most sensitive portions of a workload, encryption support to enhance data and VM protection as well as physical protection to avoid unauthorized access.</li> <li>Infrastructure Manager (ISM) enables organizations to have centralized control over the infrastructure that includes servers, storage, networking management software as well as power and cooling using a single user interface.</li> </ul>
<p><b>POWER YOUR APPLICATIONS</b></p> <ul style="list-style-type: none"> <li>32 memory slots in total supporting 8 TB memory with DDR5 DIMM modules (@ 4,800 MT/s) for improved workload performance.</li> </ul>	
<p><b>EASY EXPANDABILITY</b></p> <ul style="list-style-type: none"> <li>Our server systems are built to scale easily to be able to adapt to a variety of applications and meet future demands. PRIMERGY RX2530 M7 comes with adapters via OCP v3 as well as flexible PCIe riser cards with support for up to 3x PCIe 5.0 / 1x PCIe 4.0 (dedicated for internal RAID Controller) slots. Different available base units with 4x 3.5-inch SAS/SATA, up to 8x/10x 2.5-inch SAS/SATA/NVMe support provide enormous expandability.</li> </ul>	
<p><b>COMPREHENSIVE PROTECTION</b></p> <ul style="list-style-type: none"> <li>PRIMERGY servers are equipped with beneficial features to protect against, detect and recover from security breaches (PFR, UEFI Secure Boot, TPM 2.0, signed firmware updates, agent-free device management, secure authorization and authentication, alerting and logging, secure Out of Band Management with iRMC S6, ...).</li> </ul>	
<p><b>AGILE INFRASTRUCTURE MANAGEMENT</b></p> <ul style="list-style-type: none"> <li>Infrastructure Manager (ISM) provides seamless, holistic management ensuring that IT infrastructures retain the dynamic flexibility required to support ever-changing business demands. Two versions of ISM are available. ISM Advanced is a powerful, fully featured version offering comprehensive infrastructure management capabilities such as support for multiple hardware configurations, physical and virtual network connection indicators and firmware baseline updates. A free entry-level version, ISM Essential, provides essential monitoring and firmware update of all supported devices, including servers, storage and network switches.</li> </ul>	

# Technical details

## PRIMERGY RX2530 M7

Base unit	PRIMERGY RX2530 M7 SFF	PRIMERGY RX2530 M7 LFF	PRIMERGY RX2530 M7 SFF	PRIMERGY RX2530 M7 SFF	PRIMERGY RX2530 M7 SFF
Housing types	Rack	Rack	Rack	Rack	Rack
Storage drive architecture	8x 2.5-inch SAS/SATA	4x 3.5-inch SAS/SATA	2.5-inch SAS/SATA	10x 2.5-inch SAS/SATA/PCIe	10x 2.5-inch SATA/NVMe
Power supply	Hot-plug	Hot-plug	Hot-plug	Hot-plug	Hot-plug
Product Type	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server

## Mainboard

Mainboard type	D3982
Chipset	Intel® C741
Processor quantity and type	1 - 2 x Intel® Xeon® Bronze 3xxx processor / Intel® Xeon® Silver 4xxx processor / Intel® Xeon® Gold 5xxx processor / Intel® Xeon® Gold 6xxx processor / Intel® Xeon® Platinum 8xxx processor

## Intel® Xeon® Bronze Processor

Intel® Xeon® Bronze 3408U (8C, 1.8 GHz, TLC: 22.5 MB, Turbo: 1.90 GHz, 16 GT/s, Mem bus: 4,000MHz, 125 W)  
 Intel® Xeon® Max Processor 9460 (40C, 2.20 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)  
 Intel® Xeon® Max Processor 9462 (32 C, 2.7 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)  
 Intel® Xeon® Max Processor 9468 (48C, 2.10 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)

## Intel® Xeon® Silver Processor

Intel® Xeon® Max Processor 9460 (40C, 2.20 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)  
 Intel® Xeon® Max Processor 9462 (32 C, 2.7 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)  
 Intel® Xeon® Max Processor 9468 (48C, 2.10 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)  
 Intel® Xeon® Silver 4410T (10C, 2.7 GHz, TLC: 26.25 MB, Turbo: 3.40 GHz, 16 GT/s, Mem bus: 4,000MHz, 150 W)  
 Intel® Xeon® Silver 4410Y (12C, 2.0 GHz, TLC: 30 MB, Turbo: 2.90 GHz, 16 GT/s, Mem bus: 4,000MHz, 150 W)  
 Intel® Xeon® Silver 4416+ (20C, 2.0 GHz, TLC: 37.5 MB, Turbo: 2.90 GHz, 16 GT/s, Mem bus: 4,000MHz, 165 W)

## Intel® Xeon® Gold Processor

Intel® Xeon® Gold 5412U (24C, 2.1 GHz, TLC: 45 MB, Turbo: 2.90 GHz, 16 GT/s, Mem bus: 4,400MHz, 185 W)  
 Intel® Xeon® Gold 5415+ (8C, 2.9 GHz, TLC: 22.5 MB, Turbo: 3.60 GHz, 16 GT/s, Mem bus: 4,400MHz, 150 W)  
 Intel® Xeon® Gold 5416S (16C, 2.0 GHz, TLC: 30 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,400MHz, 150 W)  
 Intel® Xeon® Gold 5418N (24C, 1.8 GHz, TLC: 45 MB, Turbo: 2.60 GHz, 16 GT/s, Mem bus: 4,000MHz, 165 W)  
 Intel® Xeon® Gold 5418Y (24C, 2.0 GHz, TLC: 45 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,400MHz, 185 W)  
 Intel® Xeon® Gold 5420+ (28C, 2.0 GHz, TLC: 52.5 MB, Turbo: 2.70 GHz, 16 GT/s, Mem bus: 4,400MHz, 205 W)  
 Intel® Xeon® Gold 6414U (32 C, 2.0 GHz, TLC: 60 MB, Turbo: 2.60 GHz, 16 GT/s, Mem bus: 4,800MHz, 250 W)  
 Intel® Xeon® Gold 6426Y (16C, 2.5 GHz, TLC: 37.5 MB, Turbo: 3.30 GHz, 16 GT/s, Mem bus: 4,800MHz, 185 W)  
 Intel® Xeon® Gold 6428N (32 C, 1.8 GHz, TLC: 60 MB, Turbo: 2.50 GHz, 16 GT/s, Mem bus: 4,000MHz, 185 W)  
 Intel® Xeon® Gold 6430 (32 C, 2.1 GHz, TLC: 60 MB, Turbo: 3.00 GHz, 16 GT/s, Mem bus: 4,400MHz, 270 W)  
 Intel® Xeon® Gold 6434 (8C, 3.7 GHz, TLC: 22.5 MB, Turbo: 4.10 GHz, 16 GT/s, Mem bus: 4,800MHz, 195 W)  
 Intel® Xeon® Gold 6438M (32 C, 2.2 GHz, TLC: 60 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,800MHz, 205 W)  
 Intel® Xeon® Gold 6438N (32 C, 2.0 GHz, TLC: 60 MB, Turbo: 2.70 GHz, 16 GT/s, Mem bus: 4,800MHz, 205 W)  
 Intel® Xeon® Gold 6438Y+ (32 C, 2.0 GHz, TLC: 60 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,800MHz, 205 W)  
 Intel® Xeon® Gold 6442Y (24C, 2.6 GHz, TLC: 60 MB, Turbo: 3.30 GHz, 16 GT/s, Mem bus: 4,800MHz, 225 W)  
 Intel® Xeon® Gold 6444Y (16C, 3.6 GHz, TLC: 45 MB, Turbo: 4.00 GHz, 16 GT/s, Mem bus: 4,800MHz, 270 W)  
 Intel® Xeon® Gold 6448Y (32 C, 2.1 GHz, TLC: 60 MB, Turbo: 3.00 GHz, 16 GT/s, Mem bus: 4,800MHz, 225 W)  
 Intel® Xeon® Gold 6454S (32 C, 2.2 GHz, TLC: 60 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,800MHz, 270 W)  
 Intel® Xeon® Max Processor 9460 (40C, 2.20 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)  
 Intel® Xeon® Max Processor 9462 (32 C, 2.7 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)  
 Intel® Xeon® Max Processor 9468 (48C, 2.10 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)

<b>Intel® Xeon® Platinum Processor</b>	<p>Intel® Xeon® Max Processor 9460 (40C, 2.20 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)</p> <p>Intel® Xeon® Max Processor 9462 (32 C, 2.7 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)</p> <p>Intel® Xeon® Max Processor 9468 (48C, 2.10 GHz, TLC: 60 MB, Turbo: 3.50 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)</p> <p>Intel® Xeon® Platinum 8452Y (36C, 2.0 GHz, TLC: 67.5 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,800MHz, 300 W)</p> <p>Intel® Xeon® Platinum 8458P (44C, 2.7 GHz, TLC: 82.5 MB, Turbo: 3.20 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)</p> <p>Intel® Xeon® Platinum 8460Y+ (40C, 2.0 GHz, TLC: 105 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)</p> <p>Intel® Xeon® Platinum 8462Y+ (32 C, 2.8 GHz, TLC: 60 MB, Turbo: 3.60 GHz, 16 GT/s, Mem bus: 4,800MHz, 300 W)</p> <p>Intel® Xeon® Platinum 8468 (48C, 2.1 GHz, TLC: 105 MB, Turbo: 3.10 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)</p> <p>Intel® Xeon® Platinum 8468V (48C, 2.4 GHz, TLC: 97.5 MB, Turbo: 2.90 GHz, 16 GT/s, Mem bus: 4,800MHz, 330 W)</p> <p>Intel® Xeon® Platinum 8470 (52C, 2.0 GHz, TLC: 105 MB, Turbo: 3.00 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)</p> <p>Intel® Xeon® Platinum 8470N (52C, 1.7 GHz, TLC: 97.5 MB, Turbo: 2.70 GHz, 16 GT/s, Mem bus: 4,800MHz, 300 W)</p> <p>Intel® Xeon® Platinum 8480+ (56C, 2.0 GHz, TLC: 105 MB, Turbo: 3.00 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)</p> <p>Intel® Xeon® Platinum 8490H (60C, 1.9 GHz, TLC: 112.5 MB, Turbo: 2.90 GHz, 16 GT/s, Mem bus: 4,800MHz, 350 W)</p>
Processor notes	no mix of different processor types
Memory slots	32 (16 DIMMs per CPU, 8 channels with 2 slots per channel)
Memory slot type	DIMM (DDR5)
Memory capacity (min. - max.)	16 GB - 8 TB
Memory protection	<p>ECC</p> <p>Memory Scrubbing</p> <p>SDDC</p> <p>ADDDC (Adaptive Double DRAM Device Correction)</p> <p>Memory Mirroring support</p>
<b>Standard memory modules</b>	<p>128 GB (1 module(s) 128 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 4Rx4</p> <p>16 GB (1 module(s) 16 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 1Rx8</p> <p>256 GB (1 module(s) 256 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 8Rx4</p> <p>32 GB (1 module(s) 32 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 1Rx4</p> <p>32 GB (1 module(s) 32 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 2Rx8</p> <p>64 GB (1 module(s) 64 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 2Rx4</p>
Memory modules notes	Max capacity maybe changed.
<b>Interfaces</b>	
USB 3.x ports	5 x USB 3.0 (2x front, 2x rear, 1x internal)
Graphics (15-pin)	2 x VGA (thereof 1x front optional - not for base unit with 10x 2.5" devices)
Serial 1 (9-pin)	1 x optional (occupies PCIe slot)
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S6 (10/100/1000 Mbit/s)
Interface notes	Management LAN traffic can be switched to shared onboard LAN controller port, speed and connector is related to installed interface card.
<b>Onboard or integrated Controller</b>	
RAID controller	<p>All hardware storage controller options are described under Components</p> <p>For dedicated base units front AND rear storage drives may be connected to a single controller. Please see relevant system configurator for configuration options and restrictions.</p>
SATA Controller	1x SATA channel for ODD, 2x SATA channel for M.2, 8x SATA channel for HDD/SSD
LAN Controller	<p>Dynamic LoM via OCP slot; OCPv3 compliant</p> <p>Optional OCP adaptors:</p> <ul style="list-style-type: none"> <li>4 x 1 Gbit/s Ethernet (RJ45)</li> <li>2 x 10 Gbit/s Ethernet (RJ45)</li> <li>4 x 10 Gbit/s Ethernet (RJ45)</li> <li>2 x 10 Gbit/s SFP+</li> <li>4 x 10 Gbit/s SFP+</li> <li>2 x 25 Gbit/s SFP28</li> <li>4 x 25 Gbit/s SFP28</li> <li>2x 100 Gbit/s QSFP28</li> </ul> <p>All LAN controllers (for OCP slots and PCIe slots) are described under Components.</p> <p>For details, please refer to the relevant system configuration guide.</p>

<b>Onboard or integrated Controller</b>	
Remote management controller	Integrated Remote Management Controller (iRMC S6, 1024 MB attached memory incl. graphics controller) IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / TPM 2.0 module; TCG compliant (option)
<b>Slots</b>	
PCI-Express 5.0 x16	3 x Low profile
PCI-Express 4.0 x16	1 x Low profile
Slot Notes	Slot 4(internal): PCIe 4.0 x16 @CPU1 is dedicated for the modular RAID Controller. Slot 1: PCIe 5.0 x16 @CPU1 for low profile cards with up to 167mm length Slot 2: PCIe 5.0 x16 @CPU1 for low profile cards with up to 167mm length Slot 3: PCIe 5.0 x16 @CPU2 for low profile cards with up to 167mm length Slot 3 option: PCIe 5.0 x16 @CPU2 for full height cards with up to 167mm length (in this case, slot 2 is not available) Slot availability and population depending on selected base unit. Please see relevant configurator for details
<b>Drive bays (Base unit specific)</b>	
Storage drive bays	up to 4 x 3.5-inch, 8 x 2.5-inch, 10 x 2.5-inch base unit
Accessible drive bays	1 x 5.25/9.5mm for DVD-RW/Blu-ray
Notes accessible drives	Not for 10x 2.5-inch base unit. All possible options described in relevant system configurator.
Optional accessible drives	2x 2.5-inch hot-plug SAS/SATA rear option
<b>General system information</b>	
Number of fans	8
Fan configuration	redundant / hot-plug
Fan notes	n+1 redundant
<b>Operating panel</b>	
Operating buttons	On/off switch Reset button NMI button ID button
Status LEDs	At system front side: Power (DC-On: green / AC-On: white) Global error (orange) Identification (blue) Hard disks access (green) CSS (orange) At system rear side: System status (green) Identification (blue) Global error (orange) LAN connection (green) LAN speed (green / yellow)
<b>BIOS</b>	
BIOS features	UEFI compliant Secure boot support ROM based setup utility GPT support for boot drives larger than 2.2 TB Memory Redundancy support (Mirroring) IPMI support Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions IPv4/IPv6 remote PXE & iSCSI boot support Cryptographically Signed BIOS Firmware Update HTTP and HTTPS Boot PCIe Bifurcation configurable

### Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Windows Server 2022 Datacenter
	Windows Server 2022 Standard
	Windows Server 2019 Datacenter
	Windows Server 2019 Standard
	Windows Server 2019 Essentials
	VMware vSphere™ 8.0
	VMware vSphere™ 7.0
	SUSE® Linux Enterprise Server 15
Red Hat® Enterprise Linux 8	
Operating system release link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473</a>
Operating system notes	Support of other Linux derivatives on demand Use of certified or supported operating systems and virtualization software is subject to proactive acceptance of the respective License Agreements/ EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.

### Infrastructure and Server Management

DC Infrastructure Management	Infrastructure Manager (ISM) Essential Edition Advanced Edition
Server Management	ServerView Agentless Service (SVAS) ServerView ESXi CIM Provider ServerView Installation Manager (SVIM) ServerView Update Manager Express (UME)
Management notes	For further information regarding ISM see dedicated data sheets.
Manageability link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=9e92297a-16fb-4c69-8559-e38e7b42fee6">http://docs.ts.fujitsu.com/dl.aspx?id=9e92297a-16fb-4c69-8559-e38e7b42fee6</a>

### Dimensions / Weight

Rack (W x D x H)	483 mm (Bezel) / 435 mm (Body) x 808 x 43 mm
Dimension notes	Short depth: 483 mm (Bezel) / 435 mm (Body) x 728mm x 43 mm Note: Please be aware that configuration options are different for the short depth model
Mounting Depth Rack	Std: 836.95 mm / Short depth: 756.95 mm
Height Unit Rack	1 U
19" rackmount	Yes
Weight	Std: max. 19.2 kg / Short depth: max. 16.6 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option

### Environment

Operating temperature note	PRIMERGY servers are designed for the usage with operating temperatures of up to 35°C. There could be configurations that are not able to work within this normal operation class. Please use the Fujitsu WebArchitect ( <a href="http://www.fujitsu.com/configurator/public">www.fujitsu.com/configurator/public</a> ) to get detailed information on the corresponding configurations.
Operating relative humidity	8 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe">http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe</a>
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	36 dB(A) (idle) / 44 dB(A) (operating) typical Values
Sound power (LWAd; 1B = 10dB)	5.4 B (idle) / 6.2 B (operating) typical Values
Noise notes	Noise emissions depends on operation modes, system configuration and ambient temperature.

### Electrical values

Power supply configuration	1 x hot-plug power supply or 2 x hot-plug power supply for redundancy
Hot-plug power supply redundancy	Optional
Active power (max. configuration)	2,608 W
Apparent power (max. configuration)	2635 VA
Heat emission (max. configuration)	9388.8 kJ/h (8898.9 BTU/h)

Electrical values	
Rated current max.	12A (100-127 V) / 15A (200-240 V)
Active power note	To estimate the power consumption of different configurations please use the Fujitsu WebArchitect: <a href="http://www.fujitsu.com/configurator/public">www.fujitsu.com/configurator/public</a>
Power supply	500W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 500W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 900W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 900W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 1600W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz; 100V range: 1030W 1600W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 2200W hot-plug, 94% (Platinum efficiency), 200-240V, 50 / 60Hz 2400W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 1300W hot-plug, 94% (equivalent to Platinum efficiency) –48V DC 1600W hot plug, 94% (equivalent to Platinum efficiency) 380V DC
Power supply notes	Power Safeguard adapts system performance in case the power requirements exceeds supply limits. Platinum PSUs are only for APAC/Japan market.
Compliance	
Product	PRIMERGY RX2530 M7
Model	PR200C
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronical equipment)
Germany	GS
Europe	CE
USA/Canada	NRTLc/us FCC Class A ICES-003 / NMB-003 Class A
Japan	VCCI Class A + JIS 61000-3-2
Russia	EAC
South Korea	KC
China	CCC
Australia/New Zealand	RCM
Taiwan	BSMI
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

## Components

Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I
----------------	--

## SSD SAS 2.5-inch

SSD SAS, 22.5Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 22.5Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD
SSD SAS, 22.5Gb/s, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 22.5Gb/s, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD
SSD SAS, 22.5Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 22.5Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD
SSD SAS, 22.5Gb/s, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD
SSD SAS, 22.5Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 22.5Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD
SSD SAS, 22.5Gb/s, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD
SSD SAS, 22.5Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 22.5Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD
SSD SAS, 22.5Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD
SSD SAS, 22.5Gb/s, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD
SSD SAS, 12 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD
SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD
SSD SAS, 12 Gb/s, 800 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD
SSD SAS, 12 Gb/s, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD
SSD SAS, 12 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD
SSD SAS, 12 Gb/s, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD
SSD SAS, 12 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD
SSD SAS, 12 Gb/s, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD
SSD SAS, 12 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD
SSD SAS, 12 Gb/s, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD

## SSD SAS 3.5-inch

SSD SAS, 22.5Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 22.5Gb/s, 15.36 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 22.5Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 22.5Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 22.5Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SAS, 12 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD
SSD SAS, 12 Gb/s, 800 TB, Write-Intensive, hot-plug, 3.5-inch, enterprise, 10 DWPD
SSD SAS, 12 Gb/s, 800 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 3.5-inch, enterprise, 10 DWPD
SSD SAS, 12 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD
SSD SAS, 12 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD
SSD SAS, 12 Gb/s, 3.2 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD
SSD SAS, 12 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 3.5-inch, enterprise, 10 DWPD
SSD SAS, 12 Gb/s, 1.6 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD



SSD SATA 2.5-inch

SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.4 DWPD
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.5 DWPD
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD

## SSD SATA 3.5-inch

SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.0 DWPD
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.0 DWPD
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.4 DWPD
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.5 DWPD
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.0 DWPD
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD, SED
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.0 DWPD
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 0.9 DWPD

## HDD 2.5-inch

HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise

## HDD 3.5-inch

HDD SATA, 6 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  
HDD SATA, 6 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  
HDD SATA, 6 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  
HDD SATA, 6 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  
HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical  
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical  
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical  
HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise  
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise  
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise  
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise  
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise  
HDD SAS, 12 Gb/s, 20 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  
HDD SAS, 12 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  
HDD SAS, 12 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  
HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise  
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise

## PCIe SSD &amp; SATA DOM SSD

PCIe-SSD SFF, 800 GB, Write-Intensive, hot-plug, 2.5-inch, Flash drive, 100 DWPD  
PCIe-SSD SFF, 400 GB, Write-Intensive, hot-plug, 2.5-inch, Flash drive, 100 DWPD  
PCIe-SSD SFF, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD  
PCIe-SSD SFF, 12.8 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD  
PCIe-SSD SFF, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD  
PCIe-SSD SFF, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD  
PCIe-SSD SFF, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD  
PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD  
PCIe-SSD SFF, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD  
PCIe-SSD SFF, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, Flash drive, 100 DWPD  
PCIe-SSD SFF, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD

## SED

SSD SAS, 22.5Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED  
SSD SAS, 22.5Gb/s, 15.36 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED  
SSD SAS, 22.5Gb/s, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED  
SSD SAS, 22.5Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD, SED  
SSD SAS, 22.5Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD, SED  
SSD SAS, 22.5Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED  
SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED  
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED  
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED  
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED  
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED  
HDD SAS, 12 Gb/s, 20 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED  
HDD SAS, 12 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED  
HDD SAS, 12 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED  
HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED  
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED  
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED  
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED  
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED

SCSI / SAS Controller	PSAS CP 2100-8i LP SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
	Broadcom® PSAS CP600i LP SAS Ctrl. 12 Gbit/s PCIe 3.0 x8
	Broadcom® PSAS CP600e LP SAS Ctrl. 12 Gbit/s PCIe 3.0 x8
RAID Controller	pre-configured RAID1 Array for M.2 in PDUAL,
	Fujitsu PRAID EP680i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 16 GT/s, 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3916
	Fujitsu PRAID EP680e LP, RAID 5/6 Ctrl., SAS 12 Gbit/s, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP640i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3908
	Fujitsu PRAID EP580i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP520i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP 3258-16i LP, RAID 5/6 Ctrl., SAS/SATA 24 Gbit/s, NVMe-PCIe 16 GT/s, 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU
	Fujitsu PRAID EP 3254-8i LP, RAID 5/6 Ctrl., SAS/SATA 24 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU
	Fujitsu PRAID EP 3252-8i LP, RAID 5/6 Ctrl., SAS/SATA 24 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU
	Broadcom® PRAID CP500i LP, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, No FBU support
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x Qlogic QLE2770-FJ-BK LC-style
	Fibre Channel Host Bus Adapter 2 x Qlogic QLE2772-FJ-BK LC-style
	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPE35000-M2-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPE35002-M2-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x Qlogic QLE2870-FJ-BK MMF LC-style
	Fibre Channel Host Bus Adapter 2 x Qlogic QLE2872-FJ-BK MMF LC-style
	Fibre Channel Host Bus Adapter 1 x Emulex LPE36000-M64-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x Emulex LPE36002-M64-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style
	InfiniBand HCA 1 x 200Gb/s PCIe x16 QSFP for the US market max. one IB HCA 200Gb controller can be installed ( Mellanox )
GPU computing card	NVIDIA® A2, 200GB/s, 16GB GDDR6, N/A, PCIe 4.0 x8
	-, xxxGB/s, 24GB GDDR6, N/A, PCIe 4.0 x16
	NVIDIA® T400 4GB, 4 GB, 384 cores, 4GB, N/A, PCIe x16, 3 x miniDP
Rack infrastructure	Cable Arm 1U for PRIMECENTER- and 3rd-party racks
	Rackmount kit full extraction (870mm). tool less mounting for general use, length variable 559-890mm. If consider to shipment with Rack and earthquake, suggest to fix RMK with security screw.
	Rackmount kit partial extraction (400mm). tool less mounting for general use, length variable 559-890mm.

HDD 3.5-inch	HDD SATA, 6 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
	HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
	HDD SAS, 12 Gb/s, 20 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SAS, 12 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SAS, 12 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
	HDD 3.5-inch
HDD SATA, 6 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical	
HDD SATA, 6 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical	
HDD SATA, 6 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical	
HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical	
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical	
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical	
HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise	
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise	
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise	
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise	
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise	
HDD SAS, 12 Gb/s, 20 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical	
HDD SAS, 12 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical	
HDD SAS, 12 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical	
HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical	
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical	
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise	
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise	
<b>Notes</b>	
Compatibility	If and to the extent a list of components or certain compatibilities are specified in the product data sheet, these component lists and compatibility specifications are exhaustive. Using deviating or other system components and applications together with the product may but does not necessarily have to lead to compatibility problems. A final statement and/or commitment on the compatibility of such deviating or other system components and applications can only be provided after a corresponding verification through a dedicated compatibility testing.
Continuity management	The product may in connection with and depending on the specific configuration include elements to support time- and performance-critical applications, however high availability (e.g., 99.9999%) and failsafe performance is not a standalone product feature. If and to the extent the product is to be used in such business-critical environments, it is within the sole responsibility of the user to set up the specific additional technical features (e.g., Storage Cluster), redundancies, and operational conditions as required to ensure such high availability or failsafe performance.

## Notes

Security	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.
----------	---

## Warranty

Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	<a href="http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM">http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM</a>
<b>Product Support - the perfect extension</b>	
Support Pack Options	Globally available in major metropolitan areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	at least 5 years after shipment, for details see <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a>
Service Weblink	<a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a>

# More information

## Fujitsu products, solutions & services

In addition to Fujitsu PRIMERGY RX2530 M7, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu PRIMERGY RX2530 M7, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/primergy](http://www.fujitsu.com/primergy)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2023 Fujitsu LIMITED

## Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact  
Fujitsu LIMITED

Website: [www.fujitsu.com](http://www.fujitsu.com)  
2023-12-27 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>  
Copyright 2023 Fujitsu LIMITED