Fujitsu recommends Windows 11 Pro.



Data Sheet

Fujitsu Tablet LIFEBOOK U9312X

World's Lightest Convertible With A Pen

Available in red and black, the Fujitsu LIFEBOOK U9312X is an attractively slim and lightweight 360-degree convertible. All-day battery runtime and global LTE ensure highest productivity in any place. Enterprise-grade security such as the integrated PalmSecure™ sensor, powerful performance and utmost connectivity via Intel® Thunderbolt™ 4 ensure best-in-class user experience.

Ultra-slim and lightweight Convertible

The very slim and light housing make it very comfortable to carry the device. Thanks to its 360° foldability, it can be immediately turned from a Notebook to a Tablet – and back.

- Available in red or black
- Weighing just 1 kg with a robust magnesium housing
- Durability is MIL-STD-810H tested
- Intel[®] Iris[®] Xe Graphics

Security at its best

No compromises in security and data protection – the integrated PalmSecure™ sensor turns your unique palm vein pattern into your personal key.

- Privacy Camera Shutter to keep external eyes away
- PalmSecure[™] as your personal biometrical key
- Fingerprint & Full HD IR Camera supporting Windows Hello
- SmartCard reader
- Kensington Lock support

Excellent connectivity and usability

Newest interfaces and convenient features. All ports are full-sized – even the LAN port. No adapters, that can be lost and cause additional costs, needed.

- Complete set of full-sized interfaces: HDMI, LAN and USB Type-C with Intel® Thunderbolt™ 4
- 13.3 inch FHD anti-glare touch display supporting pen input
- Pen garage with inductive charging function
- 5 MP rear camera

Convenient mobility supporting usage on the go

Highest productivity on business trips without empty batteries or waste of time

- New advanced battery with improved runtime that extents your mobile working sessions
- Anytime USB charging functionality for your peripheral devices, even when system is turned off
- Always connected and instantly ready











Components

Base unit	LIFEBOOK U9312X black	LIFEBOOK U9312X red
Operating systems		
Microsoft OS support information	After the end of the product life Fujitsu will continue to test and support all upcoming Windows releases for a period of maximum 5 years, depending on the available extension of hardware services through Fujitsu Warranty top ups. For details please see "Fujitsu Service Statement for Windows General Availability Channel" at https://support.ts.fujitsu.com/IndexProdSupport.asp?Ing=com&OpenTab=	
Operating system notes	The use of Windows Operating System is subject to acceptance of the End User License Agreement of Microsoft applicable under the relevant Microsoft program.	
Processor	Intel Core i7-1265U/32GB vPro (10 Cores, up to 4.8 GHz)	
	Intel Core i7-1265U/16GB vPro (10 Cores, up to 4.8 GHz)	
	Intel® Core™ i5-1245U processor (10 Cores, up to 4.4 GHz)	
	Intel® Core™ i5-1235U processor (10 Co	ores, up to 4.4 GHz) *
	*Processor only for retail, SMB, educat	on and government
Memory	8 GB onboard memory LPDDR4 16 GB onboard memory LPDDR4 32 GB onboard memory LPDDR4	
	No DIMM	
LCD Display	13.3" Full-HD (1920x1080) AG Touch	
Bluetooth	V5.2	
Hard disk drives (internal)	PCIe-SSD, 512 GB M.2 NVMe module, S	SED
	PCIe-SSD, 256 GB M.2 NVMe module, S	SED
	PCIe-SSD, 2 TB M.2 NVMe module, SED	
	PCIe-SSD, 1 TB M.2 NVMe module, SED	
Hard disk notes	Accessible capacity may vary, also depending on used software.	
Interface add on cards/components (optional)		
3G/4G (optional)	Quectel EM120R-GL (4G Cat.12) (Downlink speed 600 MB/s, Uplink speed 150 MB/s)	
Display	33.8 cm (13.3-inch), IPS, FHD, 1,920 x 1,080 pixel, Anti-glare touchscreen, 400 cd/m², 1000:1	
Multimedia		
Camera	Front: IR Cam (2 MP) with LED, suppor Out camera: 5 MP with autofocus on to	

Base unit

Base unit	LIFEBOOK U9312X black	LIFEBOOK U9312X red	
General system information			
Chipset	Integrated in CPU		
Supported capacity RAM (min.)	8 GB		
Supported capacity RAM (max.)	32 GB		
Memory slots	LPDDR4		
Memory notes	8 GB / 16 GB / 32 GB onboard LPDDR4x (4,266 MHz) Dual channel support		
LAN	10/100/1,000 MBit/s Intel® I219LM		

Compared a vatour information				
General system information LAN notes	Intel vPro support			
Integrated WLAN BIOS version	Intel Wi-Fi 6E AX211 & BT5.2 vPro, SRD Cat. 2			
BIOS features	UEFI Specification 2.8			
	InsydeH2O BIOS On board			
Audio type Audio codec				
Audio codec Audio features	Realtek ALC257			
MIL-STD tested	2x digital array microphones, 2x built-in speakers (stereo)			
MIL-31D lested	Yes, selected MIL-STD-810H tests passed. MIL-STD-810H test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty.			
Color	Black	Red		
Material	Magnesium	Magnesium		
Display				
Diagonal Size	33.8 cm (13.3-inch)			
Display Technology	IPS			
Display type	Anti-glare touchscreen			
Display Resolution type	FHD			
Resolution (native)	1,920 x 1,080 pixel			
Aspect ratio	16:9			
' Brightness - typical	400 cd/m ²			
Contrast - typical	1000:1			
Viewing angle (h/v) - typical	178°/178°			
Display notes	Wide-view high-bright LED display (for enhanced outdoor viewing). With magnesium display lid.			
Sensors	3-axis Accelerometer			
	Gyroscope			
	Magnetic Field Sensor			
	Compass			
Digitizer / Touch Technology	Wacom Digitizer for pen (AES) input plus capacitive 10	Ofinger multi-touch screen		
Pen	AES			
	4k pressure level Pen garage			
	inductive charging			
Graphics	3 3			
Base unit	LIFEBOOK U9312X black	LIFEBOOK U9312X red		
TFT resolution (HDMI)	up to 4,096 x 2,160 @ 60 Hz	up to 4,096 x 2,160 @ 60 Hz		
Graphics brand name	Intel® Iris® Xe Graphics (with Dual channel memory)	Intel® Iris® Xe Graphics (with Dual channel memory)		
Graphics features	4 Display Support (3 external, 1 internal)	4 Display Support (3 external, 1 internal)		
Grapines reatures	HDCP support	HDCP support		
	DirectX® 12	DirectX [®] 12		
	OpenGL® 4.5	OpenGL® 4.5		
Graphics notes	Shared memory depending on main memory size and operating system 3D accelerator			
nterfaces				
OC-in	1			
Audio: line-out / headphone	1 (combo port with audio line-in)			
Audio: line-in / microphone	1 (combo port with Audio line-out)			
nternal microphones	2x digital array microphones			
JSB 3.2 Gen1 (5 Gbps) total	2x Type-A (1 with Anytime USB charging functionality)			
USB 4.0 Gen3 (20 Gbps) total	2 x Type-C Intel® Thunderbolt™4 (with Power Delivery functionality)			
USB Type-C	2 USB 4 Gen3 Thunderbolt™4, Power Delivery (15W), DP 1.4			
HDMI	1 v2.0			
Ethernet (RJ-45)	1			

Interfaces			
Memory card slots	1 (USH-II) SD 4.0 standard		
,	SD/microSD card: 2GB		
	SDHC/microSDHC card: 32GB		
	SDXC/microSDXC card: 2TB		
	Speed Class: up to UHS-II (156MB/s)		
SmartCard slot	1 (Alara - CIM and of a mandala with intermetal 45 //TE ma	- d. d. A	
SIM card slot	1 (Nano-SIM, only for models with integrated 4G/LTE module)		
eSIM card	eSIM supported - integrated in 4G/LTE Module		
Docking connector for Port Replicator	USB Type-C		
Kensington Lock support	1		
Port Replicator interfaces (optional)			
	USB Type-C PR	Thunderbolt™ 4 PR	
DC-in	1 (19V/90W required)	1 (20V/170W required)	
Power on switch	1	1	
Audio: comments	1 Combo jack for headset usage	1 Combo jack for headset usage	
DisplayPort	1x V1.2	2x V1.4++	
VGA	1		
HDMI text	1	V 2.0b	
Interface Notes	3x Type-A - 5V/0.9A, 4.5W	2x Type-A - 5V/0.9A, 4.5W	
	1x Type-C - 15W	1x Type-A - 5V/2.4A, 12W	
	1x Type-C - Up to 60 W (PD v2.0-1.1) power output to	2x Type-C - 5V, 1.5A/4.5W charging port	
	client or 4.5W input	1x Type-C - TBT4 up to 60 W (PD v2.0-1.1), 5-20V/3.0A	
		upstream (PC), Intel AMT support (vPRO) 1x Type-C - TBT4 up to 15 W (PD v2.0-1.1), 5V/3.0A	
		downstream, power output to client	
Kensington Lock support	no	1	
Ethernet (RJ-45)	1	1 (10/100/1000 Mbit/s, 2,5 Gbps)	
Notes	Number of simultaneous used displays and its possible resolutions and frequencies depend on mobile system and		
	display interface type.		
	Please consult always also the manual of the connected	client.	
Keyboard and pointing devices			
	Backlit keyboard w/o touchstick		
	Number of keyboard keys: 85, Keyboard pitch: 19 mm, K	Ceyboard stroke: 1.5 mm	
	Multi gesture touchpad with integrated mouse button f	•	
	Touchscreen		
	Tablet Pen (AES), stored in pen garage		
Wireless technologies			
Antennas	2x dual band for WLAN, 2x for LTE, Bluetooth shared wit	h WLAN	
Bluetooth	V5.2		
Integrated WLAN	Intel Wi-Fi 6E AX211 & BT5.2 vPro, SRD Cat. 2		
WLAN encryption	WPA/WPA2/WPA3 (Wi-Fi Protected Access)		
WLAN notes	WiFi 6E is supported by Windows 11 OS only - Windows	10 OS supports WiFi 6 only.	
	Import and usage according to country-specific regulati		
Integrated WWAN	LTE Quectel EM120R-GL (Cat 12) - UMTS,LTE		
WWAN notes	Including GPS functionality		
	Import and usage according to country-specific regulations.		
	LTE Connection Manager (if configured with 4G/LTE)		
GPS	Embedded in 4G module if configured with WWAN		
Power supply			
AC Adapter	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	
	(grounded) Type-C AC-Adapter slim&light	(grounded) Type-C AC-Adapter slim&light	
AC Adapter	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	
	(grounded) Type-C AC-Adapter standard	(grounded) Type-C AC-Adapter standard	

Power supply			
AC adapter	19 V / 65 W (3.42 A)	19 V / 65 W (3.42 A)	
,	20 V / 65 W (3.25 A) Type C	20 V / 65 W (3.25 A) Type C	
Notes	65W AC adapter for usage with system/ min. 90W AC Adapter for usage with Port Replicator		
Rated voltage range	100 V - 240 V (AC Input)	100 V - 240 V (AC Input)	
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz	
1st battery	Lithium polymer battery 4-cell, 64 Wh	Lithium polymer battery 4-cell, 64 Wh	
Battery features	Quick Charge: 80% in 1h	Quick Charge: 80% in 1h	
Runtime 1st battery	11 h	11 h	
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapcocom for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.		
Dimensions / Weight / Environmental			
Dimensions (W x D x H)	309 x 214.8 x 16.9 mm		
	12.18 x 8.41 x 0.62 inch		
Weight	1,015 kg		
Weight (lbs)	2,23 lbs	-	
Weight notes	Weight may vary depending on actual configu	ration	
Operating ambient temperature	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 14		
Operating relative humidity		Running: 20 - 80% (relative humidity); Packed: 20 - 80% (relative humidity)	
Product	LIFEBOOK U9312X		
Europe	CE		
	СВ		
Compliance link	https://sp.ts.fujitsu.com/sites/certificates		
Additional Software			
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)		
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Nero (backup and burning software)		
Additional software (notes)	Use of accopanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.		
Manageability			
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 15.0 (depending on processor)		
Manageability software	DeskView Client DeskView Instant BIOS Management		

Manageability		
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management	
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) WBEM (Web Based Enterprise Management) CIM (Common Information Model) BootP (made4you)	
Manageability link	http://www.fujitsu.com/fts/manageability	
Security		
Physical Security	Kensington Lock support	
System and BIOS Security	Absolute Persistence® technology capable BIOS Optional: Trusted Platform Module (TPM 2.0) EraseDisk	
User Security	Hard disk password User and supervisor BIOS password Embedded fingerprint sensor (optional) Embedded PalmSecure™ sensor (optional) Smartcard reader (integrated) AuthConductor Client Basic (secure authentication solution)	
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.	
Packaging information		
Warranty		
Warranty period	2 years (for countries within EMEIA)	
Warranty type	Bring-in Service / Collect & Return Service (depending on country)	
Warranty Terms & Conditions	http://www.fujitsu.com/warranty	
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.	
Product Support Services - the per	fect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day	

at least 5 years after shipment, for details see https://support.ts.fujitsu.com/

http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

Spare Parts availability

Service Weblink



First Thunderbolt™ Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®).

Order Code: FPCPR401BP

The universal port can easily connect almost everything with a single cable and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.

USB Type-C Port Replicator 2



Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA. You also can charge your external USB devices without the need of any

Order Code: S26391-F3327-L100

USB Type-C AC Adapter



Recharge your notebook or tablet at work, at home or on the road with this Order Code: S26391-F3326-L502 USB Type-C power source easily.

AES Pen with replacement stylus tips



Take your creativity to the next level, with the most natural pen experience Order Code: with the AES Pen with replacement stylus tips. With pen nibs that are very \$26391-F3149-L500 thin, you can experience the writing and signing behavior of an ink pen.

Car Adapter USB-C-QC



One Car Adapter fits all.

additional charger.

Independent of your mobile device charging method this car adapter will fulfill all major requirements and standards for fast charging vendorbrandindependent notebooks and all mobile devices. The Car Adapter USB-C-QC supports USB PD with PPS, Quick Charge (QC), Apple- and Samsung charge.

Order Code: S26391-F2613-L630

More information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet LIFEBOOK U9312X, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Tablet LIFEBOOK U9312X, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/computing/pc/tablets

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.

Copyright 2022 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2022-07-01 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2022 Fujitsu Technology Solutions GmbH