

RLK8-520D4-NVR-Kit-NVR-Specifications

	<b>Model</b>	<b>RLN8-410</b>
<b>Video/Audio Input</b>	IP Video Input	PoE IP camera x 8
	Audio Input	Cameras with built-in mic
<b>Video/Audio Output</b>	HDMI Output	3840x2160, 1920x1080, 1440x900, 1280x1024, 1280x800, 1280x720, 1024x768
	VGA Output	1920x1080, 1440x900, 1280x1024, 1280x800, 1280x720, 1024x768
	Audio output	1CH RCA
<b>Decoding</b>	Live View/Playback Resolution	3840x2160, 2560x1920, 2560x1440, 2048x1536, 2304x1296, 1080p, 720p
	Video Format	H.264
	Synchronous Playback	Up to 4 channels
<b>HDD</b>	SATA Devices	1 x 2TB SATA HDD
	Maximum Capacity	8TB (Maximum 4TB HDD/Port)
	External HDD	1 x eSATA
<b>External Interface</b>	USB Interface	2 x USB 2.0
	Network Interface	RJ45,10M/100M ethernet, 8 network ports for IP camera, 1 giga network port for LAN/WAN
<b>PoE</b>	Interface	8 independent 100 Mbps PoE network interfaces
	Max. Power Consumption	25W
	Supported Standard	IEEE 802.3at
<b>Network</b>	Network Protocol	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browser Supported	IE, Firefox, Chrome
	OS Supported	PC: Windows, Mac OS; SmartPhone: iOS, Android
	Max. User Access	20 users
<b>General</b>	Power Supply	DC 48V/2A
	Power Consumption	<10W (Without HDD&PoE)
	Working Environment	Temperature: -10°C~+45°C (14°F~113°F); humidity: 10%~90%
	Dimensions (mm)	260(W) x 41(H) x 230(D)
	Weight (w/o HDD)	1.2 kg
<b>Warranty</b>	Limited Warranty <sup>2</sup>	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>